





# P6

# 6.5" PENDANT SPEAKER, BLACK [100V $|8\Omega$ ]



Low Impedance Input 100V



100V Line Input



Suspension Cable Included



Discreet Design



Easy Install



Detachable Logo

The P6 pendant speakers were designed to deliver a very powerful, clear, intelligible high-quality audio to meet the needs of your indoor and outdoor open-ceiling commercial applications. These speakers with their discreet and elegant design can be easily integrated into your retail store, restaurant, bar, warehouse, factory or any open floor layout with high or vaulted ceilings.

#### **Product Type**

Full-Range Pendant Speaker (8 $\Omega$ /100V)

#### **RMS Power**

40W

#### Sensitivity (1W, 1m)

85dB

# Transformer Taps 70V

2.5W | 5W | 10W | 20W

#### **Input Connectors**

Phoenix Type Pluggable Terminal Block

#### Construction

High-grade Rugged Polypropylene

#### Fixation

Eye Bolt for Suspension | Bracket for Wall Mount / Garden Mount (not included)

#### Accessories

Wall Bracket for P6 (not included) | Garden Accessory for P6 (not included)

#### Frequency Response (-6dB)

90Hz - 20kHz

#### **Program Power**

80W (8Ω)

#### Maximum SPL (calculated)

104dB

#### Low Frequency Driver

6.5" Polypropylene Cone Woofer

#### Recommended Amplifier

MX120 | MX350

#### **IP Rating**

IP66 (Only with Back Cover Supplied with Wall Bracket or Garden Accessory)

## Net Weight

3kg (6.61lb)

#### Nominal Coverage (-6dB)

90° Conical

#### **Nominal Impedance**

8Ω

#### Transformer Taps 100V

5W | 10W | 20W | 40W

#### High Frequency Driver

1" Silk Dome Tweeter

#### Grille

Aluminum Grille | Detachable Logo

#### Dimensions (WxHxD)

208 x 280 x 208mm (8.19" x 11" x 8.19")

## Shipping Weight

4kg (8.82lb)