



W4

4" PASSIVE SPEAKER, BLACK (PAIR)
[100V|8Ω]

-  Low Impedance Input
-  100V Line Input
-  Ver./Hor. Installation
-  Easy Install
-  Bracket Included
-  Discreet Design

The W4 two-way loudspeakers with built-in 100V transformer and 8Ω power tap are perfect for both distributed and near-field applications in environments such as retail stores, restaurants, bars, churches and gyms. The low frequencies are reproduced by a 4" direct-radiating woofer with a polypropylene cone, while the high-frequency section is based on a titanium tweeter. The speaker's design with a waveguide improves dynamics and efficiency bringing out details in everything you listen to, while reducing reflections that can color the sound. A U-bracket is included and will support your installation on the wall or ceiling.

Product Type

2-Way Passive Speaker (8Ω/100V)

Frequency Response (-6dB)

90Hz - 18kHz

Nominal Coverage (-6dB)

100° H x 100° V

RMS Power

20W

Program Power

40W

Nominal Impedance

8Ω (low impedance mode)

Sensitivity (1W, 1m)

86dB

Maximum SPL (calculated)

99dB

Transformer Taps 100V

1.25W | 2.5W | 5W | 10W

Low Frequency Driver

4" Polypropylene Cone Woofer

High Frequency Driver

0.5" Mylar Dome Tweeter

Input Connectors

Binding Posts

Recommended Amplifier

A40 | A200 | MX120 | MX350

Construction

High-grade Rugged Polypropylene

IP Rating

Indoor Use

Dimensions (WxHxD)

140 x 215 x 135mm (5.5" x 8.4" x 5.3") [W4]
| 140 x 245 x 158mm (5.5" x 9.6" x 6.2")
[W4 + U-Bracket]

Fixation

Wall U-Bracket (included)

Net Weight

1.8kg (3.97lb) [W4 + U-Bracket]

Shipping Weight

4kg (8.82lb)