









W8

8" A/W SPEAKER, BLACK (PAIR) [100V|8Ω]

-  Low Impedance Input
-  100V Line Input
-  Ver./Hor. Installation
-  Easy Install
-  Bracket Included
-  Discreet Design

The W8 all-weather two-way loudspeakers with built-in 100V transformer and 8Ω power tap are perfect for both distributed and near-field applications in environments such as retail stores, restaurants, bars, churches and gyms. The low frequencies are reproduced by a 8" direct-radiating woofer with a polypropylene cone, while the high-frequency section is based on a titanium tweeter. The speaker's design with a waveguide improves dynamics and efficiency bringing out details in everything you listen to, while reducing reflections that can color the sound. A U-bracket is included and will support your installation on the wall or ceiling.

<p>Product Type 2-Way All-Weather Passive Speaker (8Ω/100V)</p>	<p>Frequency Response (-6dB) 60Hz - 20kHz</p>	<p>Nominal Coverage (-6dB) 100° H x 100° V</p>
<p>RMS Power 60W</p>	<p>Program Power 120W</p>	<p>Nominal Impedance 8Ω (low impedance mode)</p>
<p>Sensitivity (1W, 1m) 94dB</p>	<p>Maximum SPL (calculated) 114.8dB</p>	<p>Transformer Taps 100V 10W 20W 30W 40W</p>
<p>Low Frequency Driver 8" Polypropylene Cone Woofer</p>	<p>High Frequency Driver 1" Silk Dome Tweeter</p>	<p>Input Connectors Binding Posts</p>
<p>Recommended Amplifier A200 MX120 MX350</p>	<p>Grille Aluminum Acoustically Invisible</p>	<p>Construction UV Stabilised High Grade Polypropylene</p>
<p>IP Rating IP55</p>	<p>Dimensions (WxHxD) 250 x 410 x 260mm (9.8 x 16.1 x 10.2 in) [W8] 250 x 410 x 290mm (9.8 x 16.1 x 11.4 in) [W8 + U-Bracket]</p>	<p>Fixation Wall U-Bracket (included)</p>
<p>Net Weight 5.8kg (12.79lb) [W8 + U-Bracket]</p>	<p>Shipping Weight 15kg (33.07lb)</p>	