





Pro15A

15" ACTIVE FULL-RANGE SPEAKER



Instrument Input



RCA Input



Microphone Input



AUX Input



Microphone Input



Extended Compatibility

The Pro15A is an active 15" speakers engineered specifically for installation and portable solutions with a modern and trendy design to deliver high output and dynamics, extreme linearity and fidelity at a very competitive price, making them an affordable solution for the professional market. This speaker can be an ideal solution for hotels, restaurants, bars, lounges, conference rooms, Djs and musicians among many others. This versatile speaker works equally well on tripod stands or as a flying system with a wide range of rigging points. The cabinets are constructed using premium-quality 15mm plywood with polyurethane coating. Front and speakers' protection is assured by an acoustically transparent a powdercoated steel grill with acoustical foam.

Product Type

Active Multi-Purpose Speaker

Nominal Coverage (-6dB)

 $80^{\circ}\,\text{H}\,\text{x}\,50^{\circ}\,\text{V}$ (User Rotatable)

Mixer

2 Channels

Wireless Range

10m (32.8ft)

High Frequency Driver

1" Titanium Driver | 1.7" Voice Coil

Audio Signal Outputs

Mixer Output

Power Input

AC 100V - 240V 50Hz/60Hz

Handles

Two on the sides (one on each side)

Finish

Poliurea Coating

Shipping Weight

31kg (68.3lb)

Frequency Response (-6dB)

42Hz - 20kHz

Amplifier Technology

Class D Amplifier with DSP

DSP Presets

Flat | HF Boost | Music | Wall | HPF 100Hz

Maximum SPL (calculated)

124dB / 130dB (Full-Space)

Audio Signal Inputs

BT | Microphone | Instrument | CD Player | AUX

Output Connectors

1 x XLR

Power Consumption

550W (2.3A)

Grille

Black Perforated Steel

Dimensions (WxHxD)

420 x 718 x 410mm (16.5 x 28.3 x 16.1 in)

Low Frequency Extension (-10dB)

39Hz

Amplifier Power

RMS: 800W (550W + 250W) / Peak:

Wireless Connection System

BT v4.0

Low Frequency Driver

15" Woofer | 3" Voice Coil

Input Connectors

 $2\times XLR\ /\ TRS\ combo\ |\ 1\times 3.5mm\ Stereo$ Jack | 1 x Stereo RCA

Cooling Type

Convection

Fittings

12 x M8 threaded inserts | 1 x 35mm pole

Construction

15mm multi-laminate birch ply

Net Weight

27.5kg (60.6lb)