






LAs118

REFLEX ARRAYABLE SUBWOOFER



The Front-Loaded arrayable passive subwoofer LAs118.v3 is equipped with a custom made B&C, long excursion, 18" neodymium woofer. As it shares the same rigging technology with the LA122 and LA122W, a flexible integration, both on the ground or on the top of the LA122 arrays, is possible. In addition, it may also be used in arrays consisting entirely of LAs118 subwoofers. For touring applications the Las118 can be associated to the N-RAK, a universal distribution platform for power, audio signals and network. With the dedicated factory presets, the Powersoft X8 and X4 amplified controller integrated on N-RAK constitutes an extremely advanced and precise drive system for the enclosures.

Product Type Passive Reflex Subwoofer

Peak Power 4800W (10ms)

Recommended High-Pass Filter 34Hz, 18dB/oct Butterworth

Input Connectors 2 x Neutrik NL4

Handles 2 on each side

Finish Semi-Matte Black Textured Coating

Shipping Weight 68.5kg Frequency Response (-6dB) 38Hz - 160Hz

Nominal Impedance 8Ω

Maximum SPL (calculated) 136.8dB/139.8dB (Half-Space)

Recommended Amplifier Powersoft X4, Powersoft X8

Grille Black Perforated Steel

Dimensions (WxHxD) 602 x 664 x 750 mm Program Power 2400W

Frequency / Type of X-Over 80Hz to 120Hz / 24dB/oct LR (recommended)

Low Frequency Driver 1 x 18" (460mm), 4" (100mm) VC, B&C custom speaker

Fittings Rigging system, 1, 16 x M8 threaded inserts for optional wheel kit

Construction Heavily braced, 18mm multi-laminate birch ply

Net Weight 66kg